

# **Safety Data Sheet**

# Section 1 Identification of the Substance and of the Supplier

Product Name/Identification:	SUL4R-PLUS© Boron			
Synonyms:	Gypsum, Flue Gas Desulfurization (FGD) Gypsum, Calcium Sulfate Dihydrate			
Recommended Use:	Plant nutrition			
Restrictions on Use:	Applicability for certain crops and soil types should be verified with state and local agricultural extension agents			
Manufacturer:	SUL4R-PLUS, LLC.			
Address:	12601 Plantside Drive Louisville, KY 40299			
Website:	http://sul4r-plus.com			
Phone:	844-822-8385			
Emergency phone number:	Business hours: 844-822-8385 After hours: 502-779-1114			

# Section 2 Hazards Identification

### 2.1 Classification of the Substance

GHS Classification(s) according to OSHA Hazard Communication Standard (29 CFR 1910.1200):

Not Classified

While this product is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and use of the product. This SDS should be retained and available for employees and other users of this product.

Preparation Date: 2/14/18 Page 1 of 3



### 2.2 Label Elements

Labeling according to 29 CFR 1910.1200 Appendices A, B and C				
Hazard Pictogram(s):	Not applicable.			
Signal Word:	Caution.			
Hazard Statements:	The primary route of transport is airborne, but the risk of mobility is low.  High volumes of ingestion may cause nausea and/or vomiting.			
Precautionary Statements:	Obtain special instructions before use.  Do not handle until all safety precautions have been read and			
	understood.  Wear protective gloves/protective clothing/eye protection/face protection.			
	If exposed or concerned: Get medical advice/attention.			
	Store in a secure area.			
	Dispose of contents in accordance with local, regional and national regulations.			

### 2.3 Other Hazards

None known. Product incorporates dust control agent that mitigates the presence of respirable dust.

# Section 3 Composition/Information on Ingredients

Chemical Name	CAS Number	Amount by Weight %	Hazard Classification
Synthetic Gypsum (calcium sulfate dihydrate)	10101-41-4	80-88%	Specific Target Organ Toxicity- Single Exposure (Respiratory Effects)
Ammonium Lignosulfonate (stabilizer)	8061-53-8	3-8%	Eye Irritant Category 2B Skin Irritant Category 2
Ulexite	1319-33-1	5-10%	Respiratory Effects Eye Irritant Category 2B



# Section 4 First Aid Measures

### 4.1 Description of First Aid Measures

Inhalation:	If product is inhaled and irritation of the nose or coughing occurs, remove person to fresh air. Get medical advice/attention if respiratory symptoms persist.		
Ingestion:	Drink water, induce emesis. Call a physician. Not an acute poison, if large amounts ingested treat for boric oxide exposure.		
Skin Contact:	If contact with skin occurs, wash thoroughly with neutral soap and water. Seek medical advice/attention if skin irritation, ski rashes or dermatitis develop.		
Eye Contact:	If the material gets into the eye, flush the eye under running water for at least 15 minutes. If easy to do, remove contact lenses and continue to flush with water. Seek medical advice/attention if irritation persists.		

### 4.2 Most Important Health Effects, Both Acute and Delayed

#### **Acute Effects:**

This product is not expected to result in acute hazards during normal use.

### **Chronic Effects:**

Not applicable.

### 4.3 Indication of Any Immediate Medical Attention and Special Treatment Needed

Seek first aid or call a doctor or Poison Control Center if contact with eyes occurs and irritation remains after rinsing.



# Section 5 Firefighting Measures



# NFPA Rating:

Suitable Extinguishing Media:	This product is not flammable or combustible. Use extinguishing media appropriate for fighting surrounding fire.		
Unsuitable Extinguishing Media:	Not applicable, the product is not flammable or combustible.		
Special Protective Equipment and Precautions for Firefighters:	As with any fire, wear self-contained breathing apparatus (NIOSH approved or equivalent) and full protective gear.		
Specific Hazards:	This product poses no fire-related hazard.		
Hazardous Combustion Products:	Above 1450°C this product can produce sulfur dioxide and calcium oxide (SO <sub>2</sub> and CaO).		

# Section 6 Accidental Release Measures

Personal Precautions:	Avoid inhalation and contact with skin or eyes.		
Protective Equipment:	Use personal protective equipment as recommended in Section 8. For airborne concentrations exceeding Occupational Exposure Levels (OELs), use a self-contained breathing apparatus (SCBA).		
Emergency Procedures:	Contain spill area and protect from pedestrian or vehicle traffic. Use scooping, water spraying/flushing/misting or ventilated vacuum cleaning systems to clean up spills. Do not use pressurized air.		
Methods and Materials for Containment and Cleaning Up:	Avoid generating dust. Shovel up spilled material and place suitable container. Prevent contamination of drains or waterways. Dispose in accordance with federal, state/provincial and local requirements.		



# Section 7 Handling and Storage

#### Precautions for Safe Handling and Storage:

Practice good housekeeping. Minimize dust generation and accumulation. Avoid contact with skin and eyes. Wash or vacuum clothing that has become dusty. Avoid eating, smoking, or drinking while handling the material.

# Section 8 Exposure Controls/Personal Protection

#### **8.1 Control Parameters**

Chemical Name	OSHA PEL (mg/m³)	ACGIH TLV (mg/m³)	NIOSH REL TWA (mg/m³)	CA-OSHA PEL (mg/m³)
Gypsum (calcium sulfate); based on Particles not otherwise regulated (PNOR): Total Dust	15	-	10	10
Gypsum (calcium sulfate) based on PNOR: Respirable Fraction	5	-	5	5
Ulexite	15	10	2	5

#### 8.2 Exposure Controls

#### 8.2.1 Engineering Controls

No specific controls required. Ventilate to keep airborne concentrations below exposure limits. Use of an enclosed tractor cab with particulate air filtration can reduce the risk of inhaling dusts and soils during application.

### 8.2.2 Personal Protection Equipment (PPE)

**Skin Protection**: Wear gloves and protective clothing. Wash hands with soap and water after contact with material.

**Eye Protection**: Wear protective glasses with side shields. Avoid contact lenses.

**Respiratory Protection**: Use only with adequate ventilation/personal protection. OSHA Regulations (29 CFR 1910.134 - Respiratory Protection) must be followed whenever work conditions require a respirator. A NIOSH approved particulate respirator is recommended when engineering controls are not feasible, or while engineering controls are being instituted, and if an OSHA PEL or ACGIH TLV is exceeded.

**Personal Hygiene:** Work clothing should be washed regularly. Wash hands before eating, drinking, or using tobacco products. Wash exposed skin with soap and water.



# Section 9 Physical and Chemical Properties

Property	Value	Property	Value	
Appearance (physical state, color, etc.):	Granular; tan/brown/light gray	Upper/lower flammability or explosive limits:	Not Applicable	
Odor:	None	Vapor Pressure:	Not Applicable	
Odor threshold:	Not Applicable	Vapor Density:	Not Applicable	
pH:	≤ 9 but may be as low as 4 in solution	Specific gravity or relative density:	2.19 g/cc	
Melting point/freezing point:	Not Applicable	Solubility(ies):	Soluble in water	
Initial boiling point and boiling range:	Not Applicable	Partition coefficient: n-octane/water:	Not Applicable	
Flash point:	Not Applicable	Auto ignition temperature:	Not Applicable	
Evaporation rate:	Not Applicable	Decomposition temperature:	1450°C	
Flammability (solid, gas):	Not Applicable	Viscosity:	Not Applicable	
Physical state:	Solid	Corrosivity towards steel:	0.56 millimeters per year	



# Section 10 Stability and Reactivity

Reactivity:	Avoid contact with strong acids and strong oxidizers.
Chemical Stability:	Stable in dry environments.
Possibility of hazardous reactions:	Contact with strong acids could result in release of carbon dioxide.
Conditions to avoid:	Contact with incompatible materials (see below).
Incompatible materials:	Strong acids, aluminum (at high temperatures), diazomethane.
Hazardous decomposition products:	No hazardous decomposition up to 1450°C. Above 1450°C it could decompose to calcium oxide (CaO) and releases sulfur dioxide (SO <sub>2</sub> ) and various carbon oxides.

# Section 11 Toxicological Information

<u>Note</u>: No specific data are available for the product as a whole, so this information pertains to calcium sulfate dihydrate which composes 85-88% of the product and ulexite which may be present in the product at concentrations up to 5%.

#### **Carcinogenicity**

None known.

#### **Animal Data (Calcium Sulfate Dihydrate)**

#### **Acute Oral Toxicity**

Species: Rat (Sprague-Dawley)

Route of Administration: Oral (gavage)

Method: OECD Test Guideline 420 (Acute Oral Toxicity-Fixed dose procedure)

2,000 mg/kg body weight of test substance was administered to 4 female rats during main study (50, 300 and

2,000 mg/kg body weight administered during sighting study).

No mortality, no specific clinical signs observed during test period.

LD50 (Lethal Dose): > 2,000 mg/kg body weight

#### **Skin Irritation**

Species: Rabbit (New Zealand White)

Test Type: In vivo

Method: OECD TG 404 (Acute Dermal Irritation/Corrosion)

Exposure Period: 4 hours; 500 mg/site/rabbit

No erythema, no eschar and no edema (score of zero under OECD method: grading of skin reaction) was

observed at the skin on the backs of three rabbits during test period.



Result: Not irritating

#### **Skin Sensitization**

Species: Guinea pig (Hartley) Test Type: Buehler test

Method: OECD TG 406 (Skin Sensitization)

Exposure Period: hours/week for 3 consecutive weeks; 0.4 grams/site/guinea pig was applied topically with an occluded patch to the backs of 40 male guinea pigs. After 6 hours, the material was removed and the skin was

examined using the sensitization grading system.

Result: Not sensitizing

No acute inhalation toxicity, acute dermal toxicity, corrosiveness/irritation, or eye irritation corrosion studies are available for calcium sulfate dihydrate. Mutagenicity studies and Reproduction / Developmental Toxicity Screening Tests were negative.

# Animal Data (No toxicity data is available for Ulexite, therefore data is provided for Disodium Octaborate Tetrahydrate-Read-Across to Boric Acid)

#### **Acute Oral Toxicity**

Species: Rat (Crl:CD.BR)

Route of Administration: Oral (gavage)

Method: OECD Test Guideline 401 (Acute Oral Toxicity)

LD50 (Lethal Dose): >2,600 mg/kg body weight

#### **Acute Dermal Toxicity**

Species: Rabbit (New Zealand White)

Method: FIFRA (1982)

LD50 (Lethal Dose): >2,000 mg/kg body weight

#### **Acute Inhalation Toxicity**

Species: Rat (Sprague-Dawley)

Method: OECD Guideline 403 (Acute Inhalation Toxicity)

Exposure Period: 4 hour, whole body exposure LC50 (Lethal Concentration): >2 mg/liter

#### **Skin Irritation**

Species: Rabbit (New Zealand White)

Test Type: *In vivo* Method: FIFRA (1982)

Exposure Period: 24 hours; Occlusive; 500 mg/site/rabbit

Result: Not irritating; Primary Dermal Irritation Index (PDII) at 72 hours: 0.1

#### **Eye Irritation**

Species: Rabbit (New Zealand White)

Test Type: In vivo

Method: OECD Guideline 405 (Acute Eye Irritation/Corrosion); FIFRA 40 CFR 158 Exposure Period: Instilled 100 mg; Observed 1, 24, 48 and 72 hours, 7, 14, 21 days

Result: Slightly irritating; minor effects on the iris and conjunctiva cleared by Day 7; Not classified under EU CLP

Preparation Date: 2/14/18 Page 8 of 12



#### Skin Sensitization

Species: Guinea pig (Hartley)

Test Type: Buehler

Method: OECD TG 406 (Skin Sensitization)

Result: Not sensitizing

*In vitro* and *in vivo* mutagenicity studies were negative for boric acid. Repeat dose oral feeding studies at high doses in several species indicate that boric acid causes reproductive and developmental effects. Boric acid showed no evidence of carcinogenicity after a 103 week feeding study in mice.

# Section 12 Ecological Information

#### 12.1 Toxicity

No data available on final product.

#### 12.2 Persistence and Degradability

Not relevant for inorganic materials.

#### 12.3 Bioaccumulative Potential

No data available.

#### 12.4 Mobility in Soil

No data available.

#### 12.5 Results of PBT and vPvB Assessment

No data available.

#### 12.6 Other Adverse Effects

None known.

# Section 13 Disposal Considerations

See Sections 7 and 8 above for safe handling and use, including appropriate hygienic practices.

Recover or recycle if possible. Disposal should be in accordance with applicable local, regional, and national laws and regulations. Local regulations may be more stringent than regional or national requirements.

The information only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.



### Section 14

# **Transport Information**

UN number: Not classified as a hazardous material by U.S. Department of Transportation

(DOT) regulations.

Not applicable. UN proper shipping name: Transport hazard class(es): Not applicable. Not applicable. Packing group, if applicable:

# Section 15

# **Regulatory Information**

**TSCA Inventory Status** 

All components of this product are listed on the TSCA Inventory or are exempt from TSCA Inventory requirements.

California Proposition 65

Regulatory information: This product is not labeled for sale or use in the State of California, thus no Proposition 65 declarations are required.

State Right-to-Know (RTK) status

Component	CAS	MA <sup>1,2</sup>	NJ <sup>3,4</sup>	PA <sup>5</sup>	RI <sup>6</sup>
Gypsum;	7778-18-9 OR	Yes	Yes	Yes	No
calcium sulfate;	10101-41-4				
calcium sulfate, dihydrate					
Ulexite	1319-33-1	Yes	Yes	Yes	No

Preparation Date: 2/14/18

<sup>&</sup>lt;sup>7</sup>Massachusetts Department of Public Health, no date <sup>2</sup> 189<sup>th</sup> General Court of The Commonwealth of Massachusetts, no date <sup>3</sup> New Jersey Department of Health and Senior Services, 2010a

<sup>&</sup>lt;sup>4</sup>New Jersey Department of Health, 2010b

<sup>&</sup>lt;sup>5</sup>Pennsylvania Code, 1986

<sup>&</sup>lt;sup>6</sup>Rhode Island Department of Labor and Training, no date



#### **Section 16**

# Other Information, Including Date of Preparation or Last Revision

Date of preparation or last revision: May 2016

Acronyms and Abbreviations

ACGIH: American Conference of Industrial Hygienists

CA: California

CAS: Chemical Abstract Services
 CFR: Code of Federal Regulations
 FGD Flue Gas Desulfurization

GHS: Globally Harmonized System of Classification and Labelling

IARC: International Agency for Research on Cancer

• LC50: Concentration resulting in the mortality of 50% of an animal population

LD50: Dose resulting in the mortality of 50% of an animal population

MA: MassachusettsNA: Not Applicable

NFPA National Fire Protection Association

NIOSH: National Institute of Occupational Safety and Health

NJ: New Jersey

NTP: U.S. National Toxicology Program

OECD Organization for Economic Cooperation and Development

OEL: Occupational Exposure Limit

OSHA: Occupational Safety and Health Administration

PA: PennsylvaniaPa: Paschal

PBT: Persistent, Toxic and Bioaccumulative

PEL: Permissible exposure limit

PNOR: Particles not otherwise regulated
 PPE: Personal Protective Equipment
 RCS: Respirable Crystalline Silica
 REL: Recommended exposure limit

RI: Rhode IslandRTK: Right-to-Know

SCBA: Self-contained breathing apparatus

SDS: Safety Data Sheet

SIDS Screening Information Data Set

STOT-RE: Specific target organ toxicity-repeated exposure
 STOT-SE: Specific target organ toxicity-single exposure

TLV: Threshold limit value

TSCA: Toxic Substances Control Act
 TWA: Time-weighted average

U.S.: United States

U.S. DOT: United States of Department of Transportation
 vPvB Very Persistent and Very Bioaccumulative

Preparation Date: 2/14/18 Page 11 of 3



#### **DISCLAIMER**

The information contained herein is intended as a guide to the handling of the material and it has been prepared in good faith by technically knowledgeable personnel. It is not intended to be all-inclusive and the manner and conditions of use and handling by the end user may result in additional exposure considerations that cannot be foreseen by the manufacturer. The information contained herein is derived from sources we believe to be reliable. No warranty of any kind is given or implied and the manufacturer will not be liable for any damages, losses, injuries or consequential damages which may result from the use of or reliance on any information contained herein.

SUL4R-PLUS fertilizer is covered by U.S. Pat. 9,873,638 B2 | SUL4R-PLUS® is a registered trademark of SUL4R-PLUS, LLC